

Technical Data Sheet

PT 77 PrimeEX® Cleaner

Cleaner for the Treatment of Surfaces

Base: Solvent

Product description

PT 77 PrimeEX® is a solvent-containing special cleaner.

Application Areas

PT 77 PrimeEX® Cleaner is used to gently remove unwanted primer or PU residues from various surfaces, such as vehicle paint, side panels and dashboards.

Technical Data

Colour:	light yellow
Odour:	smells of lemon
Density:	ca. 0,9 g/cm ³
Viscosity:	ca. 3,5 mPas
Flash-off time fleece pad when sprayed 5-8 times:	ca. 15-30 minutes

Preliminary statement

Prior to application it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labelling, the relevant precautions should always be observed.

It is recommended to test the cleaner beforehand on a concealed area to be sure that it does not leave any marks on the surface.

Application

For uncured primer residues, spray PT 77 PrimeEX® directly on the area to be treated and wipe away with the fleece pad supplied. Make sure only new pads are used to avoid any recontamination.

For already cured primer residues, apply PT 77 PrimeEX® to the area to be treated by using the fleece pad supplied. Take care to cover only the contaminated area and leave for approx. 5 minutes. The dissolved primer can then be removed. Use the wooden scraper supplied to carefully remove extremely persistent or thick primer residues. If the area still shows contaminations, then treat it again with PT 77 PrimeEX® using a new fleece pad. Repeat this procedure until all contaminations are removed. Then finally clean the area with a standard glass cleaner.

PU residues on unprimed surfaces: Allow the residues to cure. The longer the residues are cured, the better the contamination can be removed. Uncured impurities can be removed by using PT 77 PrimeEX® and a fleece pad. Be careful, causes smearing! Already dried residues can be removed in layers from the surface by using PT 77 PrimeEX® and a fleece pad.

Note: Do not apply on heated surfaces or in sunlight. When applied, do not leave longer than 10 minutes max.

Storage

Frost-sensitive:	no
Recommended storage temperature:	15 °C to 25 °C
Shelf life:	12 months in original packaging

Note: Shake well before use. Keep away from ignition sources, hot surfaces, sparks, open flames - no smoking.

Container/packaging units

PT 77 PrimeEX® Cleaner is supplied as a set with the following content:

- 1 x PT 77 PrimeEX® Cleaner spray bottle 100 ml
- 10 x Wooden scrapers to remove persistent primer or PU residues
- 50 x Fleece pads with high absorption capacity

**Hazard Indications/
Safety Recommendations/
Transport Regulations**

see Safety Data Sheet

This Technical Data Sheet supersedes all previous editions.

Disclaimer

Note:

The above information, in particular the suggestions for processing and use of our products, is based on our knowledge and experience in standard cases. To ensure that the above information in the technical data sheets can be complied with and the respective product used or processed properly, the products need to be stored correctly. In addition, the above information reflects our state of knowledge at the time of printing this note. We are constantly striving to improve our products, and as such reserve the right to make changes to product specifications and processing instructions. The most current technical data sheet at the time of processing/application shall apply. The user must therefore always check the suitability of the products for the intended application and obtain advance information of any changes to the product specifications at PMA/TOOLS. We would like to point out the following: In particular where our products are processed and used without observing the product specification and without complying with the current processing instructions, there will be no warranty for the processed or used product unless the customer (who processed the product) can prove that an alleged defect of the product was already present (i.e. independent of processing or use) when the risk passed from us to him as the customer. Due to the different materials, substrates and different working conditions when processing or using the product, no liability for any working results will be accepted in other regards, except where that we have provided an express assurance for a working result. We would like to point out that any such additional assurance would have to be presented and, if necessary, proved by the party relying on it, i.e. by the party asserting a warranty. In all other respects, our general terms and conditions apply.