

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

PMA/TOOLS Impact filler, 20 ml

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

PMA/TOOLS AG, Siemensring 42, 47877 Willich, Germany
 Phone:+49 (0) 2154-9222-30, Fax:+49 (0) 2154-9222-55
 www.pma-tools.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (PMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H335-May cause respiratory irritation. H315-Causes skin irritation. H318-Causes serious eye damage. H317-May cause an allergic skin reaction. H411-Toxic to aquatic life with long lasting effects.

P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves and eye protection / face protection.
 P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

Exo-1,7,7-trimethylbicyclo-[2.2.1]hept-2-yl methacrylate
 Dodecyl methacrylate
 hydroxypropyl methacrylate (isomers mixture)
 Acrylic acid

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 03.07.2017 / 0004
 Replacing version dated / version: 09.07.2015 / 0003
 Valid from: 03.07.2017
 PDF print date: 04.07.2017
 PMA/TOOLS Impact filler, 20 ml

3.1 Substance

n.a.

3.2 Mixture

Exo-1,7,7-trimethylbicyclo-[2.2.1]hept-2-yl methacrylate	
Registration number (REACH)	01-2119886505-27-XXXX
Index	---
EINECS, ELINCS, NLP	231-403-1
CAS	7534-94-3
content %	<25
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 3, H412

Dodecyl methacrylate	
Registration number (REACH)	---
Index	607-247-00-9
EINECS, ELINCS, NLP	205-570-6
CAS	142-90-5
content %	<20
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

hydroxypropyl methacrylate (isomers mixture)	
Registration number (REACH)	01-2119490226-37-XXXX
Index	607-125-00-5
EINECS, ELINCS, NLP	248-666-3
CAS	27813-02-1
content %	<20
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319 Skin Sens. 1, H317

Acrylic acid	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	607-061-00-8
EINECS, ELINCS, NLP	201-177-9
CAS	79-10-7
content %	<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1A, H314 Aquatic Acute 1, H400 (M=1) Eye Dam. 1, H318

Tetradecyl methacrylate	
Registration number (REACH)	---
Index	607-134-00-4
EINECS, ELINCS, NLP	219-835-9
CAS	2549-53-3
content %	<3
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315

Hexadecyl methacrylate	
Registration number (REACH)	---
Index	607-134-00-4
EINECS, ELINCS, NLP	219-672-3
CAS	2495-27-4
content %	<3
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	
Registration number (REACH)	01-2119513212-58-XXXX
Index	---
EINECS, ELINCS, NLP	219-784-2
CAS	2530-83-8
content %	<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

eyes, reddened

Watering eyes

reddening of the skin

rash

Dermatitis (skin inflammation)

Inhalation:

Irritation of the respiratory tract

Coughing

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Protect from direct sunlight.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Do not pour remainders back into the storage vessels.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.
 Protect from direct sunlight and warming.
 Protect from light.
 Store in a well ventilated place.
 Store in a dry place.
 Store cool.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Acrylic acid	Content %:<5
WEL-TWA: 10 ppm (29 mg/m3) (EU)	WEL-STEL: 20 ppm (59 mg/m3) (10) (EU)	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Exo-1,7,7-trimethylbicyclo-[2.2.1]hept-2-yl methacrylate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	4,66	µg/l	
	Environment - sediment, freshwater		PNEC	0,604	mg/kg	
	Environment - soil		PNEC	0,118	mg/kg	
	Environment - sewage treatment plant		PNEC	2,45	mg/l	

hydroxypropyl methacrylate (isomers mixture)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,904	mg/l	
	Environment - marine		PNEC	0,904	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,972	mg/l	
	Environment - sediment, freshwater		PNEC	6,28	mg/kg	
	Environment - sediment, marine		PNEC	6,28	mg/kg	
	Environment - soil		PNEC	0,727	mg/kg	
Consumer	Human - dermal	Long term	DNEL	2,5	mg/kg	
Consumer	Human - inhalation	Long term	DNEL	8,8	mg/m3	
Consumer	Human - oral	Long term	DNEL	2,5	mg/kg	
Workers / employees	Human - dermal	Long term	DNEL	4,2	mg/kg	
Workers / employees	Human - inhalation	Long term	DNEL	14,7	mg/m3	

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sediment		PNEC	0,79	mg/kg dry weight	
	Environment - soil		PNEC	0,13	mg/kg dry weight	
Consumer	Human - dermal	Short term, systemic effects	DNEL	12,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	43,5	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	43,5	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	147	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	21	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	147	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	21	mg/kg bw/day	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 03.07.2017 / 0004
 Replacing version dated / version: 09.07.2015 / 0003
 Valid from: 03.07.2017
 PDF print date: 04.07.2017
 PMA/TOOLS Impact filler, 20 ml

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

$\geq 0,4$

Permeation time (penetration time) in minutes:

≥ 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light yellow
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>100 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	n.a.
Upper explosive limit:	n.a.
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,1 g/cm ³
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Effects of light as well as warmth.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 03.07.2017 / 0004
 Replacing version dated / version: 09.07.2015 / 0003
 Valid from: 03.07.2017
 PDF print date: 04.07.2017
 PMA/TOOLS Impact filler, 20 ml

10.5 Incompatible materials

Avoid contact with oxidizing agents.
 Avoid contact with strong alkalis.
 Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

PMA/TOOLS Impact filler, 20 ml						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Risk of serious damage to eyes.
Respiratory or skin sensitisation:						Sensitising (skin contact)
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Exo-1,7,7-trimethylbicyclo-[2.2.1]hept-2-yl methacrylate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit		Mild irritant, Does not conform with EU classification.
Serious eye damage/irritation:						Not irritant, Does not conform with EU classification.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	25	mg/kg	Rat		OECD 421

Dodecyl methacrylate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>87250	mg/kg	Mouse		
Symptoms:						respiratory distress, coughing, gastrointestinal disturbances, mucous membrane irritation

hydroxypropyl methacrylate (isomers mixture)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Not irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:						Yes (skin contact)
Respiratory or skin sensitisation:				Human being		Skin Sens. 1
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:					OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	300	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No, Analogous conclusion

Acrylic acid						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1300	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	295-750	mg/kg	Rabbit		
Symptoms:						respiratory distress, cornea opacity, coughing, mucous membrane irritation

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	8025	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	5,3	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:	NOAEL	1500	mg/kg/d			
Aspiration hazard:						No
Symptoms:						acidosis, drop in blood pressure, vomiting, headaches, cramps, dizziness, visual disturbances, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	500	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,225	mg/kg	Rat	OECD 412 (Subacute Inhalation Toxicity - 28-Day Study)	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

PMA/TOOLS Impact filler, 20 ml							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Exo-1,7,7-trimethylbicyclo-[2.2.1]hept-2-yl methacrylate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,79	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>2,57	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,233	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	2,28	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	70	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	

Dodecyl methacrylate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other information:	BOD5		1656	mg/l			
Other information:	COD		2438	mg/g			

hydroxypropyl methacrylate (isomers mixture)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	48h	493	mg/l	Leuciscus idus	DIN 38412 T.15	
12.1. Toxicity to daphnia:	EC50	48h	380	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	24,1-45,2	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>97,2	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	97,2	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	94,2	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Anaerobe decomposition., Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,97				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	>1140	mg/l	Pseudomonas putida		

Acrylic acid							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	222	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	27	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	27	mg/l	Salmo gairdneri		
12.1. Toxicity to daphnia:	EC50	48h	47	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	0,13	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:		28d	81	%			

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	30	mg/l	Cyprinus caprio	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to fish:	LC50	96h	55	mg/l	Brachydanio rerio	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to daphnia:	EC50	48h	324	mg/l	Daphnia magna	U.S. EPA ECOTOX Database	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	7d	119	mg/l	Anabaena flos-aquae	U.S. EPA ECOTOX Database	
12.1. Toxicity to algae:	NOEC/NOEL	7d	<50	mg/l	Anabaena flos-aquae	U.S. EPA ECOTOX Database	
12.2. Persistence and degradability:		28d	37	%	activated sludge	Regulation (EC) 440/2008 C.4-A (DETERMINATION OF 'READY' BIODEGRADABILITY - DOC DIE-AWAY TEST)	Not readily biodegradable
12.2. Persistence and degradability:	DOC	28d	37	%		Regulation (EC) 440/2008 C.4-A (DETERMINATION OF 'READY' BIODEGRADABILITY - DOC DIE-AWAY TEST)	Not readily biodegradable
12.3. Bioaccumulative potential:							Not to be expected
12.3. Bioaccumulative potential:	Log Pow		0,5				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	NOEC/NOEL	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: 3082

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DODECYL METHACRYL ATE)

14.3. Transport hazard class(es): 9
 14.4. Packing group: III
 Classification code: M6
 LQ: 5 L
 14.5. Environmental hazards: environmentally hazardous
 Tunnel restriction code: -



Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DODECYL METHACRYLATE)
 14.3. Transport hazard class(es): 9
 14.4. Packing group: III
 EmS: F-A, S-F
 Marine Pollutant: Yes
 14.5. Environmental hazards: environmentally hazardous



Transport by air (IATA)

14.2. UN proper shipping name:
 Environmentally hazardous substance, liquid, n.o.s. (DODECYL METHACRYLATE)
 14.3. Transport hazard class(es): 9
 14.4. Packing group: III
 14.5. Environmental hazards: environmentally hazardous



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing maternity protection and the protection of young people at work!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): < 5 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 4, 8, 11, 12, 14, 15
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.
 Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG)

1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 03.07.2017 / 0004
 Replacing version dated / version: 09.07.2015 / 0003
 Valid from: 03.07.2017
 PDF print date: 04.07.2017
 PMA/TOOLS Impact filler, 20 ml

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.
 H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H335 May cause respiratory irritation.
 H400 Very toxic to aquatic life.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
 Skin Irrit. — Skin irritation
 Eye Dam. — Serious eye damage
 Skin Sens. — Skin sensitization
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Eye Irrit. — Eye irritation
 Aquatic Acute — Hazardous to the aquatic environment - acute
 Flam. Liq. — Flammable liquid
 Acute Tox. — Acute toxicity - inhalation
 Acute Tox. — Acute toxicity - dermal
 Acute Tox. — Acute toxicity - oral
 Skin Corr. — Skin corrosion

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential

IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
IBC (Code)	International Bulk Chemical (Code)
IC	Inhibitory concentration
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
LC	lethal concentration
LC50	lethal concentration 50 percent kill
LCLo	lowest published lethal concentration
LD	Lethal Dose of a chemical
LD50	Lethal Dose, 50% kill
LDLo	Lethal Dose Low
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute of Occupational Safety and Health (United States of America)
NOAEC	No Observed Adverse Effective Concentration
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level
ODP	Ozone Depletion Potential
OECD	Organisation for Economic Co-operation and Development
org.	organic
PAH	polycyclic aromatic hydrocarbon
PBT	persistent, bioaccumulative and toxic
PC	Chemical product category
PE	Polyethylene
PNEC	Predicted No Effect Concentration
POCP	Photochemical ozone creation potential
ppm	parts per million
PROC	Process category
PTFE	Polytetrafluorethylene
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No.	9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID	Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT	Self-Accelerating Decomposition Temperature
SAR	Structure Activity Relationship
SU	Sector of use
SVHC	Substances of Very High Concern
Tel.	Telephone
ThOD	Theoretical oxygen demand
TOC	Total organic carbon
TRGS	Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG	United Nations Recommendations on the Transport of Dangerous Goods
VbF	Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC	Volatile organic compounds
vPvB	very persistent and very bioaccumulative
WEL-TWA, WEL-STEL	WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO	World Health Organization
wwt	wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.